


Bucket-Sort and Radix-Sort



Bucket-Sort



- Let be S be a sequence of n (key, element) entries with keys in the range $[0, N - 1]$
- Bucket-sort uses the keys as indices into an auxiliary array B of sequences (buckets)

Phase 1: Empty sequence S by moving each entry (k, o) into its bucket $B[k]$

Phase 2: For $i = 0, \dots, N - 1$, move the entries of bucket $B[i]$ to the end of sequence S

- Analysis:**
 - Phase 1 takes $O(n)$ time
 - Phase 2 takes $O(n + N)$ time
- Bucket-sort takes $O(n + N)$ time

Algorithm *bucketSort*(S, N)

Input sequence S of (key, element) items with keys in the range $[0, N - 1]$

Output sequence S sorted by increasing keys

$B \leftarrow$ array of N empty sequences

while $\neg S.empty()$

$(k, o) \leftarrow S.front()$

$S.eraseFront()$

$B[k].insertBack((k, o))$

for $i \leftarrow 0$ **to** $N - 1$


while $\neg B[i].empty()$

$(k, o) \leftarrow B[i].front()$

$B[i].eraseFront()$

$S.insertBack((k, o))$


Example



- Key range $[0, 9]$



Phase 1



Phase 2



Properties and Extensions



- Key-type Property**

- The keys are used as indices into an array and cannot be arbitrary objects
- No external comparator

- Stable Sort Property**

- The relative order of any two items with the same key is preserved after the execution of the algorithm

Extensions

- Integer keys in the range $[a, b]$
 - Put entry (k, o) into bucket $B[k - a]$
- String keys from a set D of possible strings, where D has constant size (e.g., names of the 50 U.S. states)
 - Sort D and compute the rank $r(k)$ of each string k of D in the sorted sequence
 - Put entry (k, o) into bucket $B[r(k)]$

Lexicographic Order



- ◆ A d -tuple is a sequence of d keys (k_1, k_2, \dots, k_d) , where key k_i is said to be the i -th dimension of the tuple
- ◆ Example:
 - The Cartesian coordinates of a point in space are a 3-tuple
- ◆ The lexicographic order of two d -tuples is recursively defined as follows

$$(x_1, x_2, \dots, x_d) < (y_1, y_2, \dots, y_d)$$



$$x_1 < y_1 \vee x_1 = y_1 \wedge (x_2, \dots, x_d) < (y_2, \dots, y_d)$$

I.e., the tuples are compared by the first dimension, then by the second dimension, etc.

Lexicographic-Sort

- ◆ Let C_i be the comparator that compares two tuples by their i -th dimension
- ◆ Let $stableSort(S, C)$ be a stable sorting algorithm that uses comparator C
- ◆ Lexicographic-sort sorts a sequence of d -tuples in lexicographic order by executing d times algorithm $stableSort$, one per dimension
- ◆ Lexicographic-sort runs in $O(dT(n))$ time, where $T(n)$ is the running time of $stableSort$

Algorithm *lexicographicSort*(S)

Input sequence S of d -tuples


Output sequence S sorted in lexicographic order

for $i \leftarrow d$ **downto** 1
 $stableSort(S, C_i)$

Example:

(7,4,6) (5,1,5) (2,4,6) (2, 1, 4) (3, 2, 4)
 (2, 1, 4) (3, 2, 4) (5,1,5) (7,4,6) (2,4,6)
 (2, 1, 4) (5,1,5) (3, 2, 4) (7,4,6) (2,4,6)
 (2, 1, 4) (2,4,6) (3, 2, 4) (5,1,5) (7,4,6)

Radix-Sort



- ◆ Radix-sort is a specialization of lexicographic-sort that uses bucket-sort as the stable sorting algorithm in each dimension
- ◆ Radix-sort is applicable to tuples where the keys in each dimension i are integers in the range $[0, N - 1]$
- ◆ Radix-sort runs in time $O(d(n + N))$


Algorithm *radixSort*(S, N)

Input sequence S of d -tuples such that $(0, \dots, 0) \leq (x_1, \dots, x_d)$ and $(x_1, \dots, x_d) \leq (N - 1, \dots, N - 1)$ for each tuple (x_1, \dots, x_d) in S

Output sequence S sorted in lexicographic order

for $i \leftarrow d$ **downto** 1
 $bucketSort(S, N)$

Radix-Sort for Binary Numbers




- ◆ Consider a sequence of n b -bit integers
 $x = x_{b-1} \dots x_1 x_0$
- ◆ We represent each element as a b -tuple of integers in the range $[0, 1]$ and apply radix-sort with $N = 2$
- ◆ This application of the radix-sort algorithm runs in $O(bn)$ time
- ◆ For example, we can sort a sequence of 32-bit integers in linear time

Algorithm *binaryRadixSort*(S)

Input sequence S of b -bit integers

Output sequence S sorted
 replace each element x of S with the item $(0, x)$

for $i \leftarrow 0$ **to** $b - 1$
 replace the key k of each item (k, x) of S with bit x_i of x
 $bucketSort(S, 2)$



Example

◆ Sorting a sequence of 4-bit integers

