

YUM Repository Configuration RHEL 8

Every Linux administrator should learn these commands

Prepared for:
In Public Interest

Prepared by:
Ankam Ravi Kumar

Follow Me on Social Networking Sites

[Facebook](#) | [Twitter](#) | [Reddit](#) | [LinkedIn](#) | [Website](#) | [Blog](#) | [YouTube](#) | [Github](#)

[Join Telegram Group](#)

Reach me over Email: aravikumar48@gmail.com

If you think this document helpful, [donate](#) a dollar as complementary

Table of Contents

RHEL 8 Yum repository	2
Mount RHEL 8 Installation Media	2
YUM Repository configuration	3

RHEL 8 Yum repository

Yellowdog Updater, Modified (YUM) configuration in RHEL 8. Red Hat Enterprise Linux Version 8 includes AppStream as a new repository so YUM configuration is little different than actual. Let's see How to configure RHEL 8 YUM Repository step by step.

Mount RHEL 8 Installation Media

By default installation media will get AppStream and BaseOS packages. First mount the DVD media into RHEL 8 server using below command (Assuming your CD/DVD drive /dev/sr0). You must have sudo privileges or become root user to mount.

```
# mount /dev/sr0 /mnt
```

Create new directory in where ever you want to dump entire RPM packages Example: /repo

```
# mkdir /repo
```

Copy the entire content of DVD media using below command

```
# cp -Rv /mnt/BaseOS /repo/  
# cp -Rv /mnt/AppStream /repo/
```

Now check /repo directory

```
# cd /repo/
# ls -ltr
total 0
dr-xr-xr-x. 4 root root 38 Jul 24 01:47 BaseOS
dr-xr-xr-x. 4 root root 38 Jul 24 01:48 AppStream
```

YUM Repository configuration

Switch directory to `/etc/yum.repos.d/` and create `.repo` files

```
# cd /etc/yum.repos.d/
# vi BaseOS.repo
[BaseOSRepo]
name=BaseOS
baseurl=file:///repo/BaseOS/
enabled=1
gpgcheck=0

## Create another repo file with file extension .repo
# vi AppStream.repo
[AppStreamRepo]
name=AppStream
baseurl=file:///repo/AppStream/
enabled=1
gpgcheck=0
```

Now check yum repolist

```
# yum repolist
Updating Subscription Management repositories.
Unable to read consumer identity
This system is not registered to Red Hat Subscription Management. You can use
subscription-manager to register.
Last metadata expiration check: 0:00:01 ago on Wed 24 Jul 2019 01:55:06 AM EDT.
repo id repo name status
AppStreamRepo AppStream 4,672
BaseOSRepo BaseOS 1,658
```

Here no need to run `createrepo` command since BaseOS and AppStream has repo data directories with XML configs already.

Related Links: [Add LUN from Storage to Linux](#) [Join Linux to Active Directory for authentication](#)