

#include <stdio.h>
FILE *fopen(char *filename, char * mode) – Opening a file (mode: “r” reading – “w” writing – “a” append)
FILE *freopen(char *filename, char * mode, FILE *file_pointer) – Reassign a file pointer to a different file
int fclose(FILE *file_pointer) – Closing a file
int ffeof(FILE *file_pointer) – Checks if end-of-file has been reached.
int fflush(FILE *file_pointer) - Empties file's buffer.
int getchar(void) – Reads a character from “stdin” (keyboard)
int fgetc(FILE *file_pointer) – Gets a character from a file
char *gets(char *buffer) - Reads a line from “stdin” (keyboard)
char *fgets(char *string, int maxchar, FILE *file_pointer) - Reads a line from a file
int printf(char *format_string, ...) – Writes formatted output on “stdout” (screen)
int fprintf(FILE *file_pointer, char *format_string, ...) – Writes formatted output on a file.
int sprintf(char *string, char *format_string, ...) – Writes formatted output on a string.
int fputc(int c, FILE *file_pointer) – Writes a character on a file.
int putchar(int c) – Writes a character on “stdout” (screen).
int puts(char *string) - Writes a string on “stdout” (screen).
int fputs(char *string, FILE *file_pointer) - Writes a string on a file.
int scanf(char *format_string, args) – Reads formatted input from “stdin” (keyboard)
int fscanf(FILE *file_pointer, char *format_string, args) – Reads formatted input from a file.

int sscanf(char *buffer, char *format_string, args) – Reads formatted input from a string.
EOF – end of file (constant with negative value)
NULL - null pointer (value 0)
#include <stdlib.h>
double atof(char *string) – Converts a string into a floating point value.
int atoi(char *string) – Converts a string into an integer value.
int atol(char *string) – Converts a string into a long integer value.
void exit(int val) – Terminates the program returning the value ‘val’.
EXIT_FAILURE – constant highlighting the unsuccessful termination of the program with exit(); non zero value.
EXIT_SUCCESS - constant highlighting the successful termination of the program with exit(); zero value.
#include <string.h>
char *strcpy(char *s1, char *s2) - Copies s2 in s1. Returns s1
char *strncpy(char *s1, char *s2, size_t n) – Copies the first “n” characters of s2 in s1. Returns s1.
int strcmp(char *s1, char *s2) - Compares s1 and s2 to determine the alphabetical order (<0, s1 precedes s2, 0 equal, >0 s1 follows s2)
int strncmp(char *s1, char *s2, size_t n) – Compares the first “n” characters of two strings.
int strlen(char *string) – Determines the length of a string.
char *strcat(char *s1, char *s2, size_t n) - Links s2 to s1. Returns s1
char *strncat(char *s1, char *s2, size_t n) - Links “n” characters of s2 to s1. Returns s1
char *strchr(char *string, int c) – Finds the first occurrence of the character ‘c’ in string;

returns a pointer to the first occurrence of c in s, NULL if not present.
char *strchr(char *string, int c) – Finds the last occurrence of the character ‘c’ in string.
char* strstr(char* s, char* t) – Returns a pointer to the first occurrence of t in s. returns NULL if not present.
char* strtok(char* s, const char* t) – Decomposes s in tokens, the characters that limit the tokens are contained in t. returns the pointer to the token (NULL if any is found). At the first call the string to be decomposed is s and the characters delimiting the various tokens in t. To operate on the same string, at following calls NULL has to be passed instead of s.
#include <ctype.h>
int isalnum(int c) – True if ‘c’ is alphanumeric.
int isalpha(int c) – True if ‘c’ is an alphabetic character.
int iscntrl(int c) – True if ‘c’ is a control character.
int isdigit(int c) – True if ‘c’ is a decimal digit.
int islower(int c) - True if ‘c’ is lowercase.
int isprint(int c) - True if ‘c’ is a printable character.
int ispunct(int c) - True if ‘c’ is a punctuation character.
int isspace(int c) - True if ‘c’ is a space character.
int isupper(int c) - True if ‘c’ is uppercase.
tolower(int c) – Converts ‘c’ to lowercase.
int toupper(int c) – Convert ‘c’ to uppercase.

#include <math.h>
int abs (int n) – integer absolute value
long labs(long n) – long absolute value
double fabs (double x) – absolute value of x
double acos(double x) - arccosine
double asin(double x) - arcsin
double atan(double x) - arctangent

double atan2(double y, double x) – arctangent of y/x.
double ceil(double x) – round up value of x.
double floor(double x) – round down value of x.
double cos(double x) – cos (x in radians)
double sin(double x) – sin (x in radians)
double tan(double x) – tan (x in radians)
double cosh(double x) – hyperbolic cosine
double sinh(double x) – hyperbolic sin
double tanh(double x) – hyperbolic tangent
double exp(double x) - e^x
double log(double x) - log(x).
double log10 (double x) – logarithm base 10
double pow (double x, double y) - x^y
int rand (void) – random integer between 0 and RND_MAX.
int random(int max_num) – random value between 0 and max_num.
void srand(unsigned seed) – initialize the sequence of random values
double sqrt(double x) – square root
#include <limits.h>
INT_MAX – Maximum value that can be represented by int variable.
INT_MIN – Minimum value that can be represented by int variable.
LONG_MAX - Maximum value that can be represented by long variable.
LONG_MIN - Minimum value that can be represented by long variable.
#include <float.h>
FLT_MAX, DBL_MAX - Maximum value that can be represented by float (or double) variable.
FLT_MIN, DBL_MIN - Minimum value that can be represented by float (or double) variable.